

OS2

Italian elegance
for doors and
windows

compasso
d'oro award

This catalog presents the OS2 window and door system, a product by Secco Sistemi and winner of the Compasso d'Oro award. It was born from the experience the company has gained in designing windows and doors with a minimal visual impact, crafted from precious metals for architecture.

An overview of the opportunities that OS2 offers to architectural design, summarizing 70 years of expertise in the fields of restoration and contemporary architecture.



ADI COMPASSO D'ORO
Winner 25 th Award



Index

6	Values
8	Design
18	Materials
42	Technology
46	Variants
50	Types of opening
52	<i>windows</i>
66	<i>doors</i>
80	<i>lift and slide doors</i>
90	<i>pivot</i>
100	<i>folding</i>
110	<i>anti-burglary</i>
122	Accessories
124	<i>handles</i>
126	<i>glazing beads</i>
128	<i>hinges</i>
130	<i>water drain</i>
138	<i>advice</i>



Ditton House
designer: Surman Weston

OS2 values

OS2 takes its name from the classification for the restoration of artworks, reminding us of its dedication to the architecture of the past, which is the result of a long and fruitful relationship with designers. With its clean lines, innovative opening types, and original accessories, OS2 also integrates with contemporary architecture.

The OS2 window and door system stands out for its elegance and artisanal attention to detail, but above all, for the successful balance between the transparency of the glass and the solid lightness of the frame made from precious metals such as brass, Corten steel, stainless steel, and galvanized steel.



OS2 design

The foundation of the system is its accurate draw, awarded with "Compasso d'Oro", the design's Oscar, with the following motivation of the jury. «The relationship between the opening and the transparent surface have always been one of the challenges of the fenestration industry. OS2 lays down a new standard by combining thermal cut and insulation, with extremely small dimensions and a interesting aesthetic flexibility thanks to the profiles in Corten, steel and burnished brass».

OS2 provides 70 different profiles to realize the preferred design of the frame, allowing to release designer's creativity and to "returning to draw the frame".


1. handles in the same material as the profile
2. glazing beads of various shapes
3. central section for the two sashes of only 62mm
4. reduced hinges, same material as the profiles
5. lateral section only 47 mm
6. constant profiles on the whole perimeter




profile design *examples*



Double casement window with 47 mm sections constant around the perimeter and a central mullion of 62 mm.




Double casement windows with constant 62 mm sections, both around the perimeter and in the central mullion.




profile design *examples*



Window frame with non-coplanar glass panes and highlighted openings. **Variant 1** of OS2 for old window-type frames.




Window frame with coplanar glass panes and undifferentiated profiles between fixed and opening sections, making the openings imperceptible. **Variant 2** of OS2 for Secco-type frames.



profile design *examples*



Vertical pivot window frame with constant sections around the perimeter and concealed hinges.




Fixed glass wall with constant profiles around the perimeter and the horizontal division.




profile design *examples*



Double-leaf door with constant profiles, including the central mullion and floor section.



Single-leaf window with consistent joints around the entire perimeter, including the fixed bottom section.



OS2 materials

The OS2 profiles are made in solid and tenacious materials with certified quality of oxidation and corrosion resistance. Materials for Secco are a source of design too, with them natural surfaces they affect the appearance of the frame and they can catch light or reflect it, they can have warm colors or austere ones and at the same time they have non-homogeneous surfaces for a continuous variant that emphasises the craftsmanship aspect of the product. All the used metals are 100% recyclable and they have high durability to concretize the sustainability of the product.






scotch brite stainless steel

316L (marine)

iron-chrome alloy nickel
and molybdenum,
cold rolled with
scotch brite finish



blackened stainless steel

316L (marine)

iron-chrome alloy nickel
and molybdenum, cold
rolled with hand
burnished finish



satin brass

CuZn33 CW506L

OT67 copper and zinc alloy,
cold rolled and
roughened, with
satin finish



patinated brass

CuZn33 CW506L

OT67 copper and zinc alloy,
cold rolled and
roughened,
hand-burnished

OS2 *materials*



galvanised steel

DX51D Z200 / ZM120

Hot galvanized Iron alloy of carbon with Sendzimir system, skinpast finish. Requires liquid or powder coating



Corten steel

Fe 510 X

Carbon iron alloy with high corrosion resistance (Cor) and tensile yield strength (ten), with oxidized finish





satin brass



blackened stainless steel



blackened stainless steel



patinated brass



satin brass

patinated brass



patinated brass



corten steel



patinated brass



satin brass



corten steel



painted galvanised steel



painted galvanised steel



corten steel



galvanised steel



corten steel



painter galvanised steel



corten steel


OS2 technology

The result of years of experience, the OS2 technology supports the design and at the same time it allows to have high performance even with minimal profiles and fixtures with large dimensions, large estate and a great insulator.

The thermal break profiles of OS2 are made of two metal shells (cold profiled) joined together by extruded polyamide (9) made integral to the parts by polyurethane resin (8). Water and air seals are guaranteed by open joint gaskets (5, 6, 7).

The handling and closing hardware, made specifically for OS2, is placed in a window chamber (4) the glazing beads (1) are fixed to the frame with concealed hook.

1. glazing bead
2. glazing slot
up to 58 mm
3. internal and external overlap
4. hardware groove
5. Internal
rebate gasket
6. external
rebate gasket
7. central
flipper gasket
8. structural thermal
break - polyurethane
9. structural thermal
break - polyamide





Harella House - London
designer: Piercy & Company

OS2 variants

The OS2 variants were designed to answer all the different needs of heat insulation and to allow the realization of new types of opening for this range of minimal profiles.

The numbers of OS2 correspond to the thickness not in profile view. Higher is the number, wider is the possibility of the window to have a thicker glass, from which derives more insulation.


OS2 85

System for the realization of windows (also tilt and turn) and doors with glass between 55 mm and 40 mm thick.



OS2 75

System for the realization of windows (also tilt and turn), doors, lift and slide, pivot, folding with glasses between 47 mm and 34 mm thick.



OS2 65

System for the realization of windows, doors, pivot, with glasses between 35 mm and 24 mm thick.



OS2 40

System for the realization of doors and fixed with glasses between 21 mm and 6.5 mm thick.






M3 - Mestre
designer: ANK architects


OS2 types of opening

The opening types developed by Secco Sistemi are not only dictated by tradition but also aim to contribute to the harmony of the building's façade, make spaces more usable, and address projects in contemporary or restoration architecture.


OS2 offers the usual opening types with new profiles and technologies, with the goal of "redesigning the window and door system".




windows **p. 52**




doors **p. 66**




lift and slide doors **p.80**



pivot **p. 90**



folding **p. 100**



anti-burglary **p. 110**

windows OS2

The window or properly “window frames”, is the essential element of a building and with OS2 it can become, with elegance, the main character.

The OS2 window has new features for this typology of profiles: the central node is only 62 mm wide, lateral node 47 mm, the OS2 can have internal and external opening and the tilt and turn opening.



VARIANTS	85	75	65	40
maximum achievable performance				
air permeability	4	4	4	x
water tightness	9A	9A	8A	x
wind resistance	C5	C5	C4	x
thermal transmittance *	1,1	1,1	1,4	x
acoustic performance	45 dB	45 dB	43 dB	x
glass thickness	55	47	35	x
tilt and turn (maximum capacity)	150	150	x	x

* standard frame with $U_g = 1,0 \text{ W/m}^2\text{K}$


technical dr.
p. 58

technical dr.
p. 60


technical dr.
p. 62

x = unavailable

GEOMETRY AVAILABLE



internal opening



external opening



OS2 75 - burnished stainless steel
external view



OS2 75 - burnished stainless steel
internal view







OS2 65 - corten steel
external view











OS2 65 - corten steel
internal view

windows *OS2 85*

inward-
opening
sections









outward-
opening
sections









windows OS2 75

inward-
opening
sections





outward-
opening
sections








windows OS2 65

inward-opening sections



outward-opening sections





Fondaco dei Tedeschi - Venice
designer: Rem Koolhaas

doors OS2

OS2 doors are made, for design continuity, with profiles that have the same dimension of the windows, lateral node is only 47 mm wide and the central node 62 mm.

The hinges, a fundamental element for the functionality and durability of the window and door system, are custom-made and have the same finishes as the profiles.




VARIANTS	85	75	65	40
maximum achievable performance				
air permeability	4	4	4	4
water tightness	7A	7A	7A	x
wind resistance	B3	B3	B3	A2
thermal transmittance*	1,0	1,1	1,4	x
acoustic performance	47 dB	47 dB	47 dB	x
glass thickness	55	47	35	x

* standard frame with Ug = 1,0 W/m²K


technical dr. p. 70 technical dr. p. 72 technical dr. p. 74 technical dr. p. 76

x = unavailable

GEOMETRY AVAILABLE



internal opening



external opening





OS2 40 - painter pickled steel
external view





OS2 40 - painter pickled steel
internal view

doors *OS2 85*

inward-
opening
sections




outward-
opening
sections





doors *OS2 75*

inward-
opening
sections







outward-
opening
sections








doors OS2 65

inward-
opening
sections





outward-
opening
sections





doors *OS2 40*

inward-
opening
sections



outward-
opening
sections





Home PN - Ciudad de Mèxico
designer. Alejandro Escudero

lift and slide OS2

The OS2 lift and slide doors find the elegance in quality materials and in the accuracy of profile design, constant on all the door perimeter with dimensions of 47 mm or 62 mm, to match the windows profiles respectively to one or two doors.

The movement of the door can take place with the traditional wheels or with the innovative magnetic levitation ØG "Zero Gravity", awarded with the Oscar of design, the "Compasso d'Oro".



download the **Slide** catalogue

VARIANTS

85 75 65 40


maximum achievable performance

	85	75	65	40
air permeability	x	4	x	x
water tightness	x	9A	x	x
wind resistance	x	B3	x	x
thermal transmittance*	x	1,3	x	x
acoustic performance	x	x	x	x
glass thickness	x	51	x	x
carried with traditional system on wheel	x	400	x	x
carried with with zero gravity system	x	1000	x	x


* standard frame with $U_g = 0,7 \text{ W/m}^2\text{K}$

x : unavailable

technical dr.
p. 84/86



GEOMETRY AVAILABLE



online opening





OS2 75 AS - burnished brass
internal view


OS2 75 AS - burnished brass
external view

lift and slide OS2 75

lift and
slide doors
sections



lift and sliding example with
wheel-mounted movement
and constant 62 mm profile
around the entire sash
perimeter, also available
with magnetic levitation
movement - ØG (zero gravity)






ØG lift and slide OS2 75

lift and slide
door sections
with magnetic
levitation ØG



sliding example with
magnetic levitation
movement - ØG (zero gravity)
and constant 47 mm profile
around the entire sash
perimeter, also available with
wheel movement





Villa Feltrin - ØG (zero gravity)
designer. ANK

pivot OS2

Elegant and spectacular, the OS2 pivot with its big dimensions and its minimal profiles redefine the relation between window and frame and also between lightweight and dimentions.

The OS2 pivot is set up as a refined solution that takes from tradition its innovation, repurposing itself with valuable metals, high sealing and insulation performance and reduced visible sections: only 62 mm consistent in all the window perimeter.



download the **Pivot** catalogue


VARIANTS	85	75	65	40
maximum achievable performance				
air permeability	x	4	4	x
water tightness	x	9A	7A	x
wind resistance	x	C5	C5	x
thermal transmittance*	x	1,1	1,4	x
acoustic performance	x	44 dB	x	x
glass thickness	x	44	32	x
maximum vertical pivot capacity	x	350	100	x
horizontal pivot maximum capacity	x	250	100	x

* standard frame with Ug = 1,0 W/m²K
x : unavailable


technical dr. technical dr.
p. 94 p. 96



GEOMETRY AVAILABLE



vertical pivot window





horizontal pivot window



pivot OS2 75



horizontal
pivot
sections

vertical
pivot
sections



pivot OS2 65

horizontal
pivot
sections





Farmhouse Crete Senesi

folding OS2

The folding opening allows to create versatile environments, which open completely to the outside.

OS2 folding solves the aesthetic and functional shortcomings of traditional windows, by offering a system with high insulation and sealing performance with visible nodes always equal to each other and of only 62 mm wide, recessed upper and lower sliding rails and high-quality profile materials.




VARIANTS	85	75	65	40
maximum achievable performance				
air permeability	x	4	x	x
water tightness	x	5A	x	x
wind resistance	x	B3	x	x
thermal transmittance*	x	1,0	x	x
acoustic performance	x	x	x	x
glass thickness	x	40	x	x

* standard frame with Ug = 0,7 W/m²K


x: unavailable

technical dr.
p. 104/106

GEOMETRY AVAILABLE



internal opening



external opening






OS2 75 LB - corten steel
internal view



OS2 75 LB - corten steel
vue intérieure




folding *OS2 75*

folding
doors
sections
with 4
inward
opening



folding OS2 75

folding
doors
sections
with 4
outward
opening





anti-burglary OS2

It is in the nature of the metal, the raw material of Secco products, the ability to resist shocks and deformations, for this reason even the small sections of OS2 feel robust enough to allow the creation of windows with minimal profiles and high anti-burglary performance up to class RC3.

The OS2 burglar-proof windows frames are made with valuable finish like stainless steel galvanized steel and the new finishes for RC, brass and Corten.




download the **RC** catalogue


VARIANTS	85	75	65	40
maximum achievable performance				
anti-burglary class 2	yes	yes	yes	x
anti-burglary class 3	yes	yes	x	x

x: unavailable


technical dr. p. 114	technical dr. p. 116	technical dr. p. 118
-------------------------	-------------------------	-------------------------




GEOMETRY AVAILABLE




inward opening windows



inward opening doors



outward opening windows






outward opening doors






anti-burglary OS2 85

window sections
two inward
opening






window sections
two outward
opening






anti-burglary OS2 75

window sections
two inward
opening






window sections
two outward
opening






anti-burglary OS2 65

window sections
two inward
opening



window sections
two outward
opening





flat in Milan
designer: Luca Bombassei


accessories

Designed and produced to complete Secco's systems, the accessories become an essential and integral part of the window and they make it unique.

Glass stoppers, handles and hinges are in harmony with the profiles of the frame because they are realized with the same finishes of profiles, that almost disappear, becoming a discrete decor element.



download the **Accessories** catalogue




handles

Elegant and discreet complements in harmony with the essential lines of the window, handles are realized with the same valuable materials and finish of profiles. The handles are available in two design family: Vitruvio and Raffaello.



download the **Accessories** catalogue



truncates

square

oval

round

raffaello




glazing beads


Little profiles to secure the glass to the frame, glazing beads are elegant elements that complete and makes unique the window design. They are available in essential geometric shapes, square, triangle, L.



download the **Accessories** catalogue




thin




gothic



triangular



square



recessed



beveled



divider
gothic glass



divider
beveled glass



divider
flat glass




hinges

Thin, light and small but able to ensure the handling of large heavy doors, hinges make up the design of the frame with elegance, they are made with the same material and finish of the profiles and they can be both technological devices and plastic elements.


The hinges are adjustable and have been tested by strict regulations that certify the quality and durability.



download the **Accessories** catalogue



two-wing
Ø 12 mm



three-wing
Ø 15 mm



welded
Ø 13 mm



water drain


Even on the outside of the window, detail becomes a value. The water drain is a fundamental device for the correct functioning of the water sealing system of the fixtures. Its geometry allows, even with adverse winds, the outflow of any water present in the window. The water drain is produced in the same finishes as the profiles of the frames and offered in two versions, traditional with a trapezoidal shape and the new round one.



download the **Accessories** catalogue


round

round water drain to be applied always in pairs



trapezoid

trapezoidal water drain with double drain





Carmel villa - California
designer. Luca studio of architecture



Border Crossing House - Polverigi
arch. Simone Subissati



Royal Greenhouses - Venice
designer: Alberto Torsello

advice

suggesting tricks to bring attention to the details that often go unnoticed, not evaluated, but which greatly affect the aesthetic and functional performance of the window and door frame

Extra clear glass whenever possible. Unlike standard glass, which often has a greenish tint, extra-clear glass preserves the window's desired appearance without alteration.

If not evaluated the warm edge is typically finished in polished aluminum. While eye-catching, this finish may disrupt the window frame's harmony. Therefore, we suggest matching the warm edge's color to either the glass seals (opaque black) or the frame itself to ensure visual cohesion across all visible components of the window frame.

Installation, the proper installation of fixtures plays a critical role in determining the window's functionality and finish. We strongly recommend entrusting the installation to experienced companies with expertise in Secco systems.

Details' always prioritize attention to detail, as it holds the key to the success of your glazing project.





Secco Sistemi is an Italian brand expression of innovation and design awarded "Compasso d'Oro".

For 70 years it contributes to the evolution of window engineering: it invents systems and profiles that become reference models for the industry and Secco continues to improve them, to interpreting projects and trends in contemporary architecture and restoration.

Secco Sistemi produces every year 1 million linear meters profiles in over 300 models that allow to realize 35 different types of openings in 4 precious metals - galvanized steel, stainless steel, corten steel and brass - and in 9 finish. It adapts its industrial capacity to the artisanal sensibility to solve and produce more than 50 special projects every year.