
FRAMELESS GLASS BALUSTRADE


CHANNEL PROFILES

BMARCHITECTURAL

FRAMELESS GLASS BALUSTRADE CHANNEL PROFILES



| | Loading (kN) |
|------------------|----------------------|
| Base Fix | 1.5 |
| Side Fix | 1.5 |
| | Glass Thickness (mm) |
| Min | 12 |
| Мах | 21.5 |
| | Finish |
| Base Fix | Satin Anodised Brush |
| Side Fix | Anodised Mil |
| Fixing Centre | 400mm for 0.74 kN |
| | & 200mm for 1.5 kN |
| Available Length | |
| 3m | |
| 6m | • |
| Page | 7-10 |








EazyFit Pro 3kN

Specification

| Loading (kN) 3 3 | Base Fix Side Fix |
|------------------------|----------------------|
| Glass Thickness (mm) | |
| 25 | Min |
| 33 | Max |
| Finish | |
| Satin Anodised Brush | Base Fix |
| Anodised Mill | Dase IIX |
| Anodised Mill | Side Fix |
| Anodised Mill | |
| 200mm | Fixing Centre |
| | Available Length |
| • | 3m |
| - | 6m |
| | |
| | |





BMARCHITECTURAL

bmarchitectural.com

EAZYLOCK 1.5KN

EAZYLOCK 1.5KN GLASS BALUSTRADE SYSTEM



TILT ADJUSTMENT

Unique engineered rotating pressure plate system enabling tilt adjustment from the balcony side resulting in faster and easier installation and perfect installation every time.

FULLY ENGINEERED


Concealed fixings can be base, side or recessed fit and available with anodised top bead or side cladding suitable for 12-21.5mm glass.

BALCONY/SINGLE SIDED INSTALLATION

Speeding up a full project installation. Eliminating the need for scaffold or expensive plant hire.



Over 4° of alignment correction





Balcony Adjustable

Tilt angle adjustable using a 19mm spanner from the safety of the balcony side, eliminating the need for plant hire.

EAZYLOCK 1.5KN COMPONENTS

EazyLock 1.5kN Channel

| 9042/3/7 | | | |
|----------|--------|----------|--------|
| Article | Finish | Fixing | Length |
| 9042 | Mill | Base fix | 3/6m |
| 9047 | Brush | Base fix | 3/6m |
| 9043 | Mill | Side fix | 3/6m |

Pre drilled. Photo shows 9042 channel.



| Clamp | Kits |
|-------|------|
|-------|------|

| Article | Glass |
|---------|---------|
| mm | |
| 9540 | 12-13.5 |
| 9541 | 15-17.5 |
| 9542 | 19-21.5 |
| 9543 | 25.5 |

Pre-packed clamps to suit 3m channel.



 Article
 Finish
 Description

 9044
 Mill
 Top Bead

 9048
 Brush
 Top Bead

 9045
 Brush
 Cladding

Top Bead + Cladding

Accessories

Length

3m 3m

3m

| Article | Description | Qty | Length mm |
|---------|-------------|------|-----------|
| 9547 | Dowels | Pair | - |
| 9548 | Divider | - | 21.5 |





End Caps

| 958 | |
|---------|------------------|
| Article | Application |
| 9586 | Clad Both Side |
| 9583 | Clad Single Side |
| 9580 | No Cladding |

| Pre-ma | de 90° (| Corner | |
|---------|----------|--------|--------|
| 9544/9 | | | |
| Article | Finish | Fixing | Length |

| Article | Finish | Fixing | Length mm |
|---------|--------|----------|-----------|
| 9544 | Mill | Base fix | 200x200 |
| 9549 | Brush | Base fix | 200x200 |
| 9545 | Mill | Side fix | 200x200 |

| EazyLock Spanner | |
|------------------|-------------|
| 19mm | |
| Article | Application |
| EL-Spanner-2 | 185mm long |

Drainage Block

| Pack | Fixing |
|------------|----------|
| Individual | Base Fix |
| | |







Drill Fixing Centres



Fixing Options

The number of fittings required to achieve the specified loadings

| Base Fixed Concrete | | | | | |
|---------------------|----|----|------|----|-------------|
| Glass kN/M | 12 | 15 | 17.5 | 19 | 21.5 SGF |
| 0.36 | 3 | 3 | 3 | 3 | |
| 0.74 | - | 3 | 3 | 3 | 4 |
| 1.5 | - | - | - | 4 | 2 |

Side Fixed Concrete

Glass kN/M

0.36 0.74

1.5

4

| Glass | 12 | 15 | 17.5 | 19 | 2 |
|-------|----|----|------|----|---|
| kN/M | | | | | S |
| 0.36 | 3 | 3 | 3 | 3 | |
| 0.74 | - | 4 | 4 | 4 | |
| 1.5 | - | - | - | - | |

Side Fixed Concrete

| | Side linea concrete | | | | |
|-------------|---------------------|----|------|----|-------------|
| 21.5 SGP | Glass kN/M | 15 | 17.5 | 19 | 21.5 SGP |
| 4 | 0.36 | - | 3 | - | 4 |
| 4 | 0.74 | - | - | 4 | 4 |
| 4 | 1.5 | - | - | - | 4 |


Bolted down into concrete at 200mm centres.

15 17.5

3

19

Bolted down into steel at 200mm centres.



EAZYLOCK 3KN GLASS BALUSTRADE SYSTEM



TILT ADJUSTMENT

Unique engineered rotating pressure plate system enabling tilt adjustment from the balcony side resulting in faster and easier installation and perfect installation every time.

FULLY ENGINEERED


Concealed fixings can be base, side or recessed fit and available with anodised top bead or side cladding suitable for 25.5mm glass.


BALCONY/SINGLE SIDED INSTALLATION

Speeding up a full project installation. Eliminating the need for scaffold or expensive plant hire.



Over 4° of alignment correction





Balcony Adjustable

Tilt angle adjustable using a 19mm spanner from the safety of the balcony side, eliminating the need for plant hire.

EAZYLOCK 3.0KN COMPONENTS

EazyLock 3.0kN Channel

| 9042/7 | , | | |
|--------------|-------------|---------------|--------|
| Article | Finish | Fixing | Length |
| 9042 | Mill | Base fix | 3/6n |
| 9047 | Brush | Base fix | 3/6m |
| Pre drilled. | Photo shows | s 9042 channe | el. |

Clamp Kits

| Article | Glass mm |
|---------|----------|
| 9543 | 25.5 |







Top Bead + Cladding

Article

9044 9048

9045

Finish

Mill Brush Mill

Description

Top Bead Top Bead Cladding

Length

3m 3m 3m



| Article | Description | Qty | Length mm |
|---------|-------------|------|-----------|
| 9547 | Dowels | Pair | - |
| 9548 | Divider | - | 21.5 |



| | Pre-ma | ade 90° | Corner | | EazyLock Span | ner | Drainage | e Block | |
|---|--------------|---------------|----------------------|--------------------|---------------|-------------|----------|------------|----------|
| | 9544/9 |) | | | 19mm | | 9550 | | |
| Application | Article | Finish | Fixing | Length mm | Article | Application | Article | Pack | Fixing |
| Clad Both Side Clad Single Side No Cladding | 9544 9549 | Mill Brush | Base fix Base fix | 200x200 200x200 | EL-Spanner-2 | 185mm long | 9500 | Individual | Base Fix |







Drill Fixing Centres



Fixing Options

6

End Caps 958 Article

9586 9583 9580


The number of fittings required to achieve the specified loadings

Base Fixed Concrete

| Glass kN/M | 25.5 SGP |
|---------------------------|---------------------|
| 3.0 | 5 |
| Bolted down into concrete | e at 200mm centres. |

| | Base Fixed Steel | |
|-------------|------------------|-------------|
| 25.5 SGP | Glass kN/M | 25.5 SGP |
| 5 | 3.0 | 5 |
| | | |

Bolted down into steel at 200mm centres.



BMARCHITECTURAL

EAZYFIT 1.5KN GLASS BALUSTRADE SYSTEM



FULLY ADJUSTABLE CLAMP SYSTEM

Easy to line-up glass

Tested up to 1.5kN (BS 6180)

Dry-glazed clamp system for clean and fast installation (no epoxy sealant required) and easy replacement of broken glass panels

Cost effective: Reduced labour time on site (Fixed every 400 or 200mm)


Light-weight & Pre-drilled profiles: Off-theshelf kit

Available as Base or Side Fix to suit 12 to 21.5mm glass

Suitable for indoor and outdoor applications (totally anodised extrusion)

Top rail (slotted tube), gaskets and connectors available ex-stock

Fully tested system for domestic and residential projects; Offices and working environment (incl. storage), restaurant & bars Image shows 1.5kN with Base Fix drilled hole (9002)




Channel Dimensions

Please see table overleaf for GLASS DEDUCTIONS depending on glass thickness.

EAZYFIT 1.5KN FITTING OPTIONS

Fully Adjustable

Quick and simple glazing angle adjustment after installation to fine tune alignment or correct any structural anomalies.




Fixing Options

Concrete Base Fixing

| Glass kN/M | 12 | 13.5 SG | 15 | 17.5 SG | 19 | 21.5 EVA | 21.5 SG |
|---------------|----|------------|----|------------|----|-------------|------------|
| 0.36 | | | - | - | - | - | - |
| 0.74 | - | - | • | • | • | • | - |
| 1.5 | - | - | - | - | • | - | |


concrete at 200mm centres



Concrete Side Fixing

| Glass kN/M | 12 | 15 | 19 | 21.5 SG |
|---------------|----|----|----|------------|
| 0.36 | • | - | • | - |
| 0.74 | - | • | • | • |
| 1.5 | - | - | - | • |

Aluminium shoe base bolted down into concrete at 200mm centres



Glass Deduction

Glass deductions FROM THE BOTTOM OF CHANNEL section to BOTTOM OF GLASS EDGE typically measure:-


| Glass Thickness mm | Glass Deduction |
|--------------------|-----------------|
| 10 | 21.5 |
| 12 | 24.5 |
| 13.5 | 23 |
| 15 | 21.5 |
| 17.5 | 22.5 |
| 19 | 22.5 |
| 21.5 | 22.5 |

Variations from measurements apply due to glass tolerances. This chart should be used as a guide only.

Steel Based Fixing


| Glass kN/M | 12 | 13.5 SG | 15 | 17.5 SG | 19 | 21.5 EVA | 21.5 SG |
|---------------|----|------------|----|------------|----|-------------|------------|
| 0.36 | | | - | - | - | - | - |
| 0.74 | - | - | • | • | • | • | • |
| 1.5 | - | - | - | - | • | - | • |

Aluminium shoe base bolted down into steel at 200mm centres with M12 - 10.9 fixings.



Steel Side Fixing

| Glass kN/M | 12 | 15 | 19 | 21.5 SG |
|---------------|----|----|----|------------|
| 0.36 | • | - | | - |
| 0.74 | - | • | • | • |
| 1.5 | - | - | - | • |




Aluminium shoe base bolted down into concrete at 200mm centres.


Timber Base Fixing

| Glass kN/M | 12 | 15 | 19 | 21.5 SG |
|---------------|----|----|----|------------|
| 0.36 | | - | - | - |
| 0.74 | - | - | - | • |
| 1.5 | - | - | - | - |
| | | | | |

Aluminium shoe base bolted down into concrete at 200mm centres



Drill Fixing Centres



Fixing centre: 400mm for 0.74kN and 200mm for 1.5Kn

EAZYFIT 1.5KN COMPONENTS

1.5kN Channel

| 9002 - Base Fix | |
|-----------------|--------|
| Article | Length |
| 9002 EFBF 3M | 3m |
| 9002 EFBF 6M | 6m |
| 9003 - Side Fix | |
| Article | Length |
| 9003 EFSF 3M | 3m |
| 9003 EFSF 6M | 6m |
| | |

Pre drilled, anodised satin stainless finish.



Top Bead

| 9004 | |
|----------------------------------|--------|
| Article | Length |
| 9004 | 3m |
| Anodised satin stainless finish. | |

Side Cladding

| 9005 | |
|----------------------------------|--------|
| Article | Length |
| 9005 | 3m |
| Anodised satin stainless finish. | |



1.5kN Black Channel

| 9002 - Base Fix | |
|--------------------|--------|
| Article | Length |
| 9002 BLACK EFBF 3M | 3m |
| 9002 BLACK EFBF 6M | 6m |




Top Bead Black

9004 Article Length 9004 BLACK 3m Anodised satin stainless finish.

Side Cladding Black

| 9005 | |
|----------------------------------|--------|
| Article | Length |
| 9005 BLACK | 3m |
| Anodised satin stainless finish. | |





Pre-made 90° Corner

| 90 | | |
|-------------|------|--------|
| Article | Туре | Finish |
| 90.9002 | Base | Satin |
| 90.9002-BLK | Base | Black |
| 90.9003 | Side | Satin |

135x135mm



Bottom Cover

| 9006 | |
|------|--|
| | |
| | |

| Article | Finish |
|------------|--------|
| 9006 | Satir |
| 9006 Black | Black |



Clamp Kits

| 94 | |
|---------|----------|
| Article | Glass mm |
| 94120 | 12 |
| 94135 | 13.5 |
| 94150 | 15 |
| 94175 | 17.5 |
| 94190 | 19 |
| 94215 | 21.5 |
| | |

Pre-packed clamps to suit 3m channel. Including: clamps; bars; bolts and gasket



Cladding Insert

| 9007 | |
|---------------------------------|--------|
| Article | Length |
| 9007 | 3m |
| Anodised satin stainless finish | |



9

EAZYFIT 1.5KN COMPONENTS CONT.

End Caps Base Fix/Raked

| Article | Fixing | |
|--------------|-------------------|------------------------------|
| 9504 | Base Fix | Bead/Bead |
| 9508 | Base Fix | Bead/Cladding |
| 9509 | Base Fix | Cladding/Cladding |
| 9511 9503 | Base Fix Raked | Bead/Bead Bead/Bead-200mm |

End Caps Side Fix

| Article | Fixing | |
|---------|----------|-----------------------|
| 9508 | Side Fix | Cladding/Bead |
| 9505-L | Side Fix | Cladding/Bottom Cover |
| 9505-R | Side Fix | Cladding/Bottom Cover |
| | | |

| Тор | Seal | Gasket | |
|-----|------|--------|--|
| iop | Jeat | Gasket | |

| PGA | |
|--------------------|------------------------|
| Article | Glass mm |
| PGA-001 PGA-002 | 12-17.5mm 19-21.5mm |

Dowels

| 9507 | |
|---------|------|
| Article | Qty |
| 9507 | Pair |









Photo shows article 9511

Timber Plate

| 9515 | |
|-----------------|------------|
| Article | Qty |
| 9515 9515-3M | Each 15 |




Spanner

| 9506 | |
|---------|------|
| Article | Qty |
| 9506 | Each |



Drainage Block

| 9510 | | |
|---------|------------|----------|
| Article | Pack | Fixing |
| 9510 | Individual | Base Fix |
| 9510SF | Individual | Side Fix |



Watertight Plate Kit

9514

| Article | Fixing |
|---------|----------|
| 9514 | Base Fix |

Pack contains 15 Drainage blocks and 2 sealant tubes.



bmarchitectural.com

EAZYFIT PRO 3KN GLASS BALUSTRADE SYSTEM

EAZYFIT PRO 3KN SIDE FIX & BASE FIX

Eazyfit Pro 3KN heavy-duty and fully adjustable 3KN commercial balustrade system, designed as a highly-durable public safety barrier for large commercial constructs.

FAST AND EASY TO INSTALL AND ADJUST

One of the most simple balustrade systems to fit and adjust thanks to its patented screw clamp technology. Dry glazed where no specialist tools are required. Glass can easily be removed and replaced if required.

FULLY ACCREDITED UP TO 3KN

Accredited and approved by multiple organisations to verify that it meets national and international building regulations for use as edge protection, where up to 3kN force loading is required.

APPROPRIATE FOR COMMERCIAL AND ANTI-TERROR USES

A 3kN force loading capability, EAZYFIT PRO is a commercially appropriate product which can be fortified using conversion kits into bomb-resistant or bullet-proof balustrade systems.



EAZYFIT PRO 3KN SIDE FIX

Fully adjustable system

Adjustable clamp to line-up glass

Tested for 3kN Base Fix (BS 6180)

Suitable for 25 to 31.5mm glass

Dry-glazed wedge system for clean installation (no arbokol required) and easy replacement of broken glass panels

No specialist tools required (13mm standard socket to adjust and tighten the clamp)

Suitable for heavy duty installations with a high volume of people traffic (sport venue or public buildings)


Pre-drilled profiles for quick installation

Available with side cladding or top bead

Suitable for indoor and outdoor applications (totally anodised extrusion)

Top rail (slotted tube or capping), gaskets and connectors available ex-stock





EAZYFIT PRO 3KN BASE FIX

Fully adjustable system

Adjustable clamp to line-up glass

Tested for 3kN Base Fix (BS 6180)

Suitable for 25 to 33mm glass

Dry-glazed wedge system for clean installation (no arbokol required) and easy replacement of broken glass panels

No specialist tools required (13mm standard socket to adjust and tighten the clamp)


Suitable for heavy duty installations with a high volume of people traffic (sport venue or public buildings)

Pre-drilled profiles for quick installation

Available with side cladding or top bead

Suitable for indoor and outdoor applications (totally anodised extrusion)


Top rail (slotted tube or capping), gaskets and connectors available ex-stock



EAZYFIT PRO 3KN FITTING OPTIONS

Fully Adjustable

Quick and simple glazing angle adjustment after installation to fine tune alignment or correct any structural anomalies.



FIXING OPTIONS

Concrete Base Fixing

| Glass | 25 | 25.5 | 31.5 | 33 |
|-------|----|------|------|-----|
| kN/M | | SG | PVB | PVE |
| 3.0 | | | | |



Steel Base Fixing

| Glass | 25 | 25.5 | 31.5 | 33 |
|-------|----|------|------|-----|
| kN/M | | SG | PVB | PVB |
| 3.0 | | | | |

Aluminium shoe base bolted down into steel at 200mm centres.



Concrete Side Fixing

| Glass | 25 | 25.5 | 31.5 | 33 |
|-------|----|------|------|-----|
| kN/M | | SG | PVB | PVB |
| 3.0 | • | • | • | |

bolted down into at iminium shoe 200mm centres




Steel Side Fixing

| Glass | 25 | 25.5 | 31.5 | 33 |
|-------|----|------|------|-----|
| kN/M | | SG | PVB | PVB |
| 3.0 | • | • | • | _ |

Aluminium shoe base bolted down into at 200mm centres



Drill Fixing Centres



Fixing centre: 200mm for 3Kn

EAZYFIT PRO 3KN COMPONENTS

EazyFit Pro 3kN Channel

| 9033 - Bas | se Fix | |
|------------------|--------|--------|
| Article | Length | Finish |
| 9033EFBF | 3m | Satin |
| Pre drilled anod | lised | |



EazyFit Pro 3kN Channel

| 9036 - Sid | e Fix | |
|-------------------|--------|--------|
| Article | Length | Finish |
| 9036EFSF | 3m | Satin |
| Pre drilled, anod | ised. | |



Clamp Kits

| 93 | |
|---------|----------|
| Article | Glass mm |
| 93250 | 25 |
| 93255 | 25.5 |
| 93315 | 31.5 |
| 93330 | 33 |

Top Bead

| Article | Length |
|---------|--------|
| 9034 | 3m |

Pre-packed clamps to suit 3m channel. Including: clamps; bars; bolts and gasket.





Base Fix Cladding

| 9035 | |
|---------|--------|
| Article | Length |
| 9035 | 3m |

Anodised satin stainless finish.

Side Fix Cladding 9037

| Article | Length |
|----------------------------------|--------|
| 9037 | 3m |
| Anodised satin stainless finish. | |

Pre-made 90° Corner

| Article | Length mm |
|---------|-----------|
| 90.9033 | 165x165 |

End Caps Base Fix

| | Application | Article |
|--------------------------------|----------------------|--------------|
| Bead/Bead | Base Fix | 9538 |
| Cladding/Cladding | Base Fix | 9539 |
| Bead/Cladding Bead/Cladding | Base Fix Side Fix | 9540 9551 |









Top Seal Gasket

| BMG | |
|--------------------|------------------------|
| Article | Glass mm |
| BMG-001 BMG-002 | 25-25.5mm 31-33.5mm |

| 9507 | |
|---------|------|
| Article | Qty |
| 9507 | Pair |
| | |





BMARCHITECTURAL

SPECIALISTS IN ARCHITECTURAL SYSTEMS

From homes to workplaces and beyond, we help create inspiring and safe spaces where people thrive.

Our expertise areas include:

- Residential, commercial and anti-terror Glass Balustrade
- Canopies, partitions and structural walls of Frameless Glass
- Fire-rated, security, slimline and thermally-insulated Steel Glazing
- Class A Fire-Rated Balcony Systems for safer high-rise living
- Composite and recycled plastic products for transforming Outdoor Spaces


Our architectural systems enhance the natural light, feeling of space, views, safety and visual appeal of a property. They also enable design professionals and building owners to meet fall protection, thermal, fire and security regulations with ease.

Contact us to discuss your requirements. We supply new-build and renovation projects, large and small, throughout the UK and Ireland.

T: 0114 254 3226

E: sales@bmarchitectural.com

W: www.bmarchitectural.com





May 2025







ANGUS F GUNN LTD

